

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: **JANUARY 15, 2002**

---

**In the Claims:**

Claims 1 to 14 (Previously Cancelled).

15. (Previously Added) A driver circuit for driving a power element connected to an inductive load, the driver circuit comprising:

an input terminal connected to a conduction terminal of the power element, and an output terminal connected to a control terminal of the power element;

a first current generator connected between a voltage reference and the output terminal for providing a first charge current to the control terminal of the power element; and

a second current generator connected in parallel with said first current generator between the voltage reference and the output terminal for providing a second charge current to the control terminal of the power element, the second charge current being based upon a voltage at the input terminal.

16. (Previously Added) A driver circuit according to Claim 15, further comprising:

a switch connected between said second current generator and the output terminal; and

a voltage sense-and-compare circuit connected between a drive terminal of said switch and the input terminal.

17. (Previously Added) A driver circuit according to Claim 16, wherein said voltage sense-and-compare circuit

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: JANUARY 15, 2002

---

comprises a sensing block, and a voltage comparator cascade connected to said sensing block.

18. (Previously Added) A driver circuit according to Claim 17, wherein said voltage comparator comprises a first input connected to an output of said sensing block, a second input connected to an internal voltage reference, and an output connected to the drive terminal of said switch.

19. (Previously Added) A driver circuit according to Claim 15, wherein the first and second charge currents have different values.

20. (Previously Added) A driver circuit according to Claim 19, wherein the first charge current is less than the second charge current.

21. (Previously Added) A driver circuit according to Claim 15, wherein said voltage sense-and-compare circuit opens said switch for disconnecting said second current generator from the output terminal when the voltage at the input terminal begins to decrease, thereby enabling the control terminal of the power element to be charged with the first charge current when the power element initiates a turn-on.

22. (Previously Added) A driver circuit according to Claim 17, wherein said sensing block differentiates the voltage at the input terminal.

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: **JANUARY 15, 2002**

---

23. (Previously Added) A driver circuit according to Claim 17, wherein said sensing block comprises a junction capacitor of a high-voltage integrated diode.

24. (Previously Added) A driver circuit according to Claim 15, wherein each of said first and current generators comprises:

    a resistor connected to the voltage reference; and  
    a transistor comprising a first conduction terminal connected to said resistor, and a second conduction terminal connected to the output terminal;

    the driver circuit further comprising a respective enabling transistor connected to a control terminal of a corresponding transistor.

25. (Previously Added) A driver circuit according to Claim 18, wherein said switch comprises a first transistor connected to the voltage reference, and said first transistor comprises a control terminal connected to the output of said voltage comparator.

26. (Previously Added) A driver circuit according to Claim 25, wherein said switch further comprises a second transistor comprising a first conduction terminal connected to the voltage reference, and a control terminal connected to a conduction terminal of said first transistor.

27. (Previously Added) A driver circuit according to Claim 26, further comprising a mirror transistor connected between a second conduction terminal of said

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: JANUARY 15, 2002

---

second transistor and said second current generator.

28. (Previously Added) A driver circuit according to Claim 18, further comprising an internal generator for generating the internal voltage reference, said internal generator being connected to the voltage reference and comprising an output connected to the second input of said voltage comparator.

29. (Previously Added) A driver circuit according to Claim 15, wherein the power element comprises an IGBT transistor, and the conduction terminal of the power element is a collector terminal of said IGBT transistor.

30. (Previously Added) A driver circuit for driving an IGBT transistor connected to an inductive load, the driver circuit comprising:

an input terminal connected to a conduction terminal of the IGBT transistor, and an output terminal connected to a control terminal of the IGBT transistor;

a first current generator connected between a voltage reference and the output terminal for providing a first charge current to the control terminal of the IGBT transistor;

a second current generator connected in parallel with said first current generator between the voltage reference and the output terminal for providing a second charge current to the control terminal of the IGBT transistor, the second charge current being based upon a voltage at the input terminal; and

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: JANUARY 15, 2002

---

a switch connected between said second current generator and the output terminal for disconnecting said second current generator from the output terminal so that the control terminal of the IGBT transistor is charged with the first charge current when the power element initiates a turn-on.

31. (Previously Added) A driver circuit according to Claim 30, further comprising a voltage sense-and-compare circuit connected between a drive terminal of said switch and the input terminal.

32. (Previously Added) A driver circuit according to Claim 31, wherein said voltage sense-and-compare circuit comprises a sensing block and a voltage comparator cascade connected to said sensing block.

33. (Previously Added) A driver circuit according to Claim 32, wherein said voltage comparator comprises a first input connected to an output of said sensing block, a second input connected to an internal voltage reference, and an output connected to the drive terminal of said switch.

34. (Previously Added) A driver circuit according to Claim 30, wherein the first and second charge currents have different values, and the first charge current is less than the second charge current.

35. (Previously Added) A driver circuit according to Claim 30, wherein said voltage sense-and-compare circuit

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: JANUARY 15, 2002

---

opens said switch for disconnecting said second current generator from the output terminal when the voltage at the input terminal begins to decrease.

36. (Previously Added) A driver circuit according to Claim 30, wherein each one of said first and current generators comprises:

- a resistor connected to the voltage reference; and
- a transistor comprising a first conduction terminal connected to said resistor, and a second conduction terminal connected to the output terminal;

the driver circuit further comprising a respective enabling transistor connected to a control terminal of a corresponding transistor.

37. (Previously Added) A driver circuit according to Claim 33, wherein said switch comprises:

- a first transistor connected to the voltage reference, and said first transistor comprises a control terminal connected to the output of said voltage comparator; and

- a second transistor comprising a first conduction terminal connected to the voltage reference, and a control terminal connected to a conduction terminal of said first transistor.

38. (Currently Amended) An electronic ignition system comprising:

- a power element; and
- a driver circuit for driving said power

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: JANUARY 15, 2002

---

element and comprising

an input terminal connected to a conduction terminal of said power element, and an output terminal connected to a control terminal of said power element,

a first current generator connected between a voltage reference and the output terminal for providing a first charge current to the control terminal of said power element, and

a second current generator connected in parallel with said first current generator between the voltage reference and the output terminal for providing a second charge current to the control terminal of said power element, the second charge current being based upon ~~on~~ a voltage at the input terminal.

39. (Previously Added) An electronic ignition system according to Claim 38, further comprising:

a switch connected between said second current generator and the output terminal; and

a voltage sense-and-compare circuit connected between a drive terminal of said switch and the input terminal.

40. (Previously Added) An electronic ignition system according to Claim 39, wherein said voltage sense-and-compare circuit comprises a sensing block, and a voltage comparator cascade connected to said sensing block.

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: JANUARY 15, 2002

---

41. (Previously Added) An electronic ignition system according to Claim 38, wherein the first charge current is less than the second charge current.

42. (Previously Added) An electronic ignition system according to Claim 39, wherein said voltage sense-and-compare circuit opens said switch for disconnecting said second current generator from the output terminal when the voltage at the input terminal begins to decrease, thereby enabling the control terminal of said power element to be charged with the first charge current when the power element initiates a turn-on.

43. (Previously Added) An electronic ignition system according to Claim 40, wherein each of said first and current generators comprises:

    a resistor connected to the voltage reference; and  
    a transistor comprising a first conduction terminal connected to said resistor, and a second conduction terminal connected to the output terminal;

    the driver circuit further comprising a respective enabling transistor connected to a control terminal of a corresponding transistor.

44. (Currently Amended) An electronic ignition system according to Claim 38, wherein said switch comprises:

    a first transistor connected to the voltage reference, and said first transistor comprises a control terminal connected to an output of said voltage ~~comparator~~  
comparator; and



In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: JANUARY 15, 2002

---

a second transistor comprising a first conduction terminal connected to the voltage reference, and a control terminal connected to a conduction terminal of said first transistor.

45. (Currently Amended) A method for driving a power element connected to an inductive load using a driver circuit comprising an input terminal connected to a conduction terminal of the power element, and an output terminal connected to a control terminal of the power element, the method comprising:

delivering a first charge current to the control terminal of the power element; and

delivering a second charge current to the control terminal of the power element, the second charge current being based upon ~~on~~ a voltage at the input terminal.

46. (Previously Added) A method according to Claim 45, wherein the first charge current is provided by a first current generator, and the second current is provided by a second current generator connected in parallel to the first current generator; the method further comprising using a switch connected between the second current generator and the output terminal for disconnecting the second current generator from the output terminal.

47. (Previously Added) A method according to Claim 46, wherein the second current generator is disconnected from the output terminal when the voltage at the input terminal begins to decrease, thereby enabling the control

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: JANUARY 15, 2002

---

terminal of the power element to be charged with the first charge current when the power element initiates a turn-on.

48. (Previously Added) A method according to Claim 46, further comprising driving the switch using a voltage sense-and-compare circuit connected between a drive terminal of the switch and the input terminal.

49. (Previously Added) A method according to Claim 46, wherein each of the first and current generators comprises:

- a resistor connected to the voltage reference; and
- a transistor comprising a first conduction terminal connected to the resistor, and a second conduction terminal connected to the output terminal;

- the driver circuit further comprising a respective enabling transistor connected to a control terminal of a corresponding transistor.

50. (Previously Added) A method according to Claim 46, wherein the switch comprises:

- a first transistor connected to the voltage reference, and the first transistor comprises a control terminal connected to an output of the voltage sense-and-compare circuit; and

- a second transistor comprising a first conduction terminal connected to the voltage reference, and a control terminal connected to a conduction terminal of said first transistor.

In re Patent Application of:  
**TORRISI ET AL.**  
Serial No. 10/050,595  
Filing Date: **JANUARY 15, 2002**

---

51. (Previously Added) A method according to Claim 45, wherein the power element comprises an IGBT transistor, and the conduction terminal of the power element is a collector terminal of the IGBT transistor.